
MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name: ACETONE
CAS number: 67-64-1
EINECS number: 200-662-2
Product code: ACE005 and ACE025P
Brand: Solmedia Ltd

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: PC21: Laboratory chemicals.

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Solmedia Ltd.
- Address of Supplier: Unit 2, Vernon Drive
Battlefield Enterprise Park
Shrewsbury
SY1 3TF
UK
- Telephone: 0844 80 80 900
- Email: labsupplies@solmedialtd.com

1.4 Emergency telephone number

Emergency Phone # +44 (0)844 80 80 900

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification under CLP:**

Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects:

Highly flammable liquid and vapour. Causes serious eye irritation.
May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Hazard statements: H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Precautionary statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P370+378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

PBT:

This product is not identified as a PBT/vPvB substance.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical identity:	ACETONE 99.5% BP
CAS number:	67-64-1
EINECS number:	200-662-2
Contains:	Molecular Formula: C ₃ H ₆ O
Molecular Weight:	58.08 g/mol

SECTION 4: First aid measures

4.1 Description of first aid measures

Skin contact:	Wash immediately with plenty of soap and water. Consult a doctor.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Wash out mouth with water. Consult a doctor.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact:	There may be mild irritation at the site of contact.
Eye contact:	There may be irritation and redness.
Ingestion:	No data available.
Inhalation:	May cause drowsiness or dizziness.
Delayed / immediate effects:	No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Dry sand. Dry chemical powder. Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Not applicable.

5.3 Advice for firefighters

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Eliminate all sources of ignition. Evacuate the area immediately. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Refer to section 8 of SDS for personal protection details.

6.2 Environmental precautions

Do not discharge into drains or rivers.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Refer to section 13 of SDS.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. Store in cool, well ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable packaging: Not applicable.

7.3 Specific end use(s)

No special requirement.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits:

Respirable dust

State	8-hour TWA	15 min. STEL	8-hour TWA	15 min. STEL
EU	1,210 mg/m ³	3,620 mg/m ³	-	-

DNEL/PNEC Values

ACETONE 99.5% BP

Type	Exposure	Value	Population	Effect
PNEC	Soil (agricultural)	33.3 mg/kg	-	-
PNEC	Marine Water	1.06 mg/l	-	-
PNEC	Fresh Water	10.6 mg/l	-	-
PNEC	Marine sediments	3.04 mg/kg	-	-
PNEC	Fresh water sediments	30.4 mg/kg	-	-
PNEC	Onsite sewage treatment plant	100 mg/l	-	-

8.2 Exposure controls**Engineering measures:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Respiratory protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection:

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Splash contact
Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

Eye protection:

Face-shield. Safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection:

Impervious clothing. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the

concentration and amount of the dangerous substance at the specific workplace.

Environmental:

Do not let product enter drains. Prevent from entering in public sewers or the immediate environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State:	Liquid
Colour:	Colourless
Boiling point/range°C:	56 °C at 1,013 hPa
Melting point/range°C:	-94 °C
Flammability limits %:	
lower:	2
upper:	13
Flash point°C:	-17.0 °C
Part.coeff. n-octanol/water:	
	log Pow: -0.24
Autoflammability°C:	465.0 °C
Vapour pressure:	245.3 hPa at 20.0 °C
Relative density:	0.791 g/mL at 25 °C

9.2 Other safety information

Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat. Flames. Sources of ignition.

10.5 Incompatible materials

Bases. Oxidising agents. Reducing agents. Acetone reacts violently with phosphorous oxychloride.

10.6 Hazardous decomposition products

In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Based on test data
STOT-single exposure	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.

Inhalation: May cause drowsiness or dizziness.

Delayed / immediate effects:

No data available.

Other information: Target Organs - Central nervous system. Eyes. Gastro-intestinal tract. Respiratory system. Lungs. Skin. Medical Considerations - Skin disorders and allergies.

SECTION 12: Ecological information

12.1 Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	5540	mg/l
DAPHNIA	96H LC50	8800	mg/l

12.2 Persistence and degradability

Readily biodegradable.

12.3 Bioaccumulative potential

No bioaccumulation potential.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This product is not identified as a PBT/vPvB substance.

12.6 Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Disposal operations:**

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste.

Handle uncleaned containers like the product itself.

Recovery operations:

Not applicable.

Disposal of packaging:

Dispose of as unused product.

NB:

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information**14.1 UN number**

UN1090

14.2 UN proper shipping name

ACETONE

14.3 Transport hazard class(es)

3

14.4 Packaging group

II

14.5 Environmental hazards**Environmentally hazardous:**

No

Marine pollutant:

No

14.6 Special precautions for user**Special precautions:**

No special precautions.

Tunnel code:

D/E

Transport category:

2

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: Other information

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3:

EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solmedia Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.