
MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name: ACID ALCOHOL 3%

Product codes:
HST306

Brand: Solmedia Ltd

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Solmedia Ltd.
- Address of Supplier: Unit 2, Vernon Drive
Battlefield Enterprise Park
Shrewsbury
SY1 3TF
UK
- Telephone: 0844 80 80 900
- Email: labsupplies@solmedialtd.com

1.4 Emergency telephone number

Emergency Phone # +44 (0)844 80 80 900

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; STOT SE 2: H371; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye irritation. Highly flammable liquid and vapour. May cause damage to organs . Harmful if swallowed.

2.2 Label elements

Label elements under CHIP:

Hazard statements: H315: Causes skin irritation. H319: Causes serious eye irritation. H225: Highly flammable liquid and vapour. H371: May cause damage to organs. H302: Harmful if swallowed.

Signal words: Danger

Hazard pictograms: GHS02: Flame, GHS07: Exclamation mark, GHS08: Health hazard



2.3 Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients:

EINECS	CAS	CHIP Classification	CLP Classification	Percent
ETHANOL				
200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq 2: H225	>70%
METHANOL				
200-659-6	67-56-1	F: R11; T: R23/24/25; T: R39/23/24/25	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<5%
HYDROGEN CHLORIDE				
231-595-7	7647-01-0		Acute Tox. 3: H331; Skin Corr. 1A:H314;	3%

SECTION 4: First aid measures

4.1 General information

IF exposed: Immediately call a POISON CENTRE/doctor/.... If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Change contaminated, saturated clothing. Do not leave affected person unattended.

After Inhalation

Immediately call a POISON CENTRE/doctor/.... Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. Contact doctor with Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye. Remove contact lenses, if present and easy to do. Continue rinsing.

In case of ingestion

Immediately call a POISON CENTRE/doctor/.... Do NOT induce vomiting. Rinse mouth thoroughly with water. Give nothing to eat or drink.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2 Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and materials for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4 Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3 Specific end use(s)

Specific end use(s): No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Hazardous ingredients:

Workplace exposure limits:

ETHANOL

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

METHANOL

UK	266 mg/m3	333 mg/m3	-	-
----	-----------	-----------	---	---

Respirable dust

HYDROGEN CHLORIDE

UK

8 mg/m³8 mg/m³**8.2 Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Personal protective equipment

Wear suitable protective clothing. When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique

(Without touching glove's outer surface) to avoid skin contact with this product. Dispose of Contaminated gloves after use in accordance with applicable laws and good laboratory practices.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min

Splash contact Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min

Wash and dry hands.

Body Protection

Impervious clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection not required. For nuisance exposures use type OV/AG (US) or type ABEK

(EU EN 14387) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Eye protection:



Goggles recommended during refilling: Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU)

Additional Information

Wash hands before breaks and after work. Avoid contact with skin and eyes. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

Control of environmental exposure

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities. If material reaches soil inform authorities responsible for such cases.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State: Liquid

9.2 Other safety information

Other information: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Stable under normal conditions. Stable at room temperature.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4 Conditions to avoid

Heat. Hot surfaces. Sources of ignition. Flames.

10.5 Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6 Hazardous decomposition products

In combustion emits toxic fumes

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Toxicity values: Not applicable.

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Symptoms/ routes of exposure

Skin contact: There may be mild irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable

SECTION 12: Ecological information**12.1 Toxicity**

Ecotoxicity values: No data available.

12.2 Persistence and degradability

Biodegradable

12.3 Bioaccumulative potential

No Bioaccumulation potential.

12.4 Mobility in soil

Readily absorbed into soil.

12.5 Results of PBT and vPvB assessment

This substance is not identified as a PBT substance

12.6 Other adverse effects

Negligible ecotoxicity.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information

14.1 UN number

UN1170

14.2 UN proper shipping name

ETHANOL (ETHYL ALCOHOL)

14.3 Transport hazard class(es)

3

14.4 Packing group

II

14.5 Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6 Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3:

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R11: Highly flammable.

R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solmedia Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.