

MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name: LEISHMAN STAIN

Product Code: DYE204
Brand: Solmedia Ltd

1.2 Relevant identified uses of the substance or mixture and uses advised against

PC21: Laboratory chemicals.

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Solmedia Ltd.

- Address of Supplier: Unit 2, Vernon Drive

Battlefield Enterprise Park

Shrewsbury SY1 3TF UK

- Telephone: 0844 80 80 900

- Email: labsupplies@solmedialtd.com

1.4 Emergency telephone number

Emergency Phone # +44 (0)844 80 80 900

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification under CHIP: F: R11; T: R23/24/25; T: R39/23/24/25

Classification under CLP: STOT SE 1: H370; Acute Tox. 3: H301+311+331; Flam. Liq. 2:

H225F:

Most important adverse effects: Highly flammable liquid and vapour. Toxic if swallowed, in

contact with skin or if inhaled. Causes damage to organs

2.2 Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

 $\label{eq:H301+311+331:Toxic if swallowed, in contact with skin or if inhaled.}$

1

H370: Causes damage to organs.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS06: Skull and crossbones

GHS08: Health hazard

February 2020





Precautionary statements:

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P321: Specific treatment (see instructions on this label).

 ${\tt P303+361+353: IF\ ON\ SKIN\ (or\ hair): Remove\ immediately\ all}$

contaminated clothing.

Rinse skin with water/shower.

P307+311: IF exposed: Call a POISON CENTER or doctor.

P311: Call a POISON CENTER or doctor.

2.3 Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHANOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-659-6	67-56-1	-	Flam. Liq 2: H225; Acute Tox.	>90%
			3: H331; Acute Tox. 3: H311;	
			Acute Tox. 3: H301; STOT SE 1:	
			H370	

SECTION 4: First aid measures

4.1 Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless

stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if

there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to

hospital for specialist examination.



Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious,

give half a litre of water to drink immediately. If unconscious, check

for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position.

Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst

doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If unconscious, check for breathing and apply artificial respiration if necessary. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be redness or whiteness of the skin in the area of

exposure. Irritation or pain may occur at the site of contact.

Absorption through the skin may be fatal.

Eye contact: There may be severe pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. There

may be vomiting. Convulsions may occur. There may be loss of

consciousness.

Inhalation: There may be shortness of breath with a burning sensation in the

throat. Absorption through the lungs can occur causing symptoms similar to those of ingestion. Convulsions may occur. There may be

loss of consciousness.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate effects can be expected after short-term exposure.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Alcohol resistant foam, Water spray, Carbon dioxide, Dry chemical powder.

Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Notify the police and fire brigade immediately. Eliminate all sources of ignition. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental precautions

Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and materials for containment and cleaning up

Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4 Reference to other sections

Refer to section 8 of SDS

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling requirements Avoid direct contact with the substance. Ensure there is exhaust ventilation of the area.

Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build-up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Hazardous ingredients:



METHANOL

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour STEL	15 min. STEL
UK	266 mg/m3	333 mg/m3	-	1

Respirable dust

DNEL / PNEC No data available

8.2 Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area. Ensure lighting and

electrical equipment is not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of

emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State: Liquid

9.2 Other safety information

Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Stable under normal conditions. Stable at room temperatures

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.



10.4 Conditions to avoid

Heat. Hot surfaces. Sources of ignition. Flames.

10.5 Incompatible materials

Strong oxidising agents. Strong acids

10.6 Hazardous decomposition products

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Hazardous ingredients:

METHANOL

INV	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (toxic)	INH DRM ING	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be redness or whiteness of the skin in the area of exposure.

Irritation or pain may occur at the site of contact. Absorption through the

skin may be fatal.

Eye contact: There may be severe pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. There may be

vomiting. Convulsions may occur. There may be loss of consciousness.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

Absorption through the lungs can occur causing symptoms similar to those of ingestion. Convulsions may occur. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable

SECTION 12: Ecological information



12.1 Toxicity

Ecotoxicity values: No data available

12.2 Persistence and degradability

Biodegradable

12.3 Bioaccumulative potential

No bioaccumulation potential.

12.4 Mobility in soil

Readily absorbed into soil

12.5 Results of PBT and vPvB assessment

This product is not identified as a PBT/vPvB substance

12.6 Other adverse effects

Negligible ecotoxicity.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal operations Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal.

SECTION 14: Transport information

14.1. UN number

UN number: UN1230

14.2. UN proper shipping name

Shipping name: METHANOL

14.3. Transport hazard class (es)

Transport class: 3 (6.1)

14.4. Packing group

Packing group:

14.5. Environmental hazards



Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: Other information

Other information: This safety data sheet is prepared in accordance with Commission

Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision

Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H301+311+331: Toxic if swallowed, in contact with skin or if

inhaled.

H311: Toxic in contact with skin.

H331: Toxic if inhaled.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is

conclusively proven that no other routes of exposure

cause the hazard>.

R11: Highly flammable.

R23/24/25: Toxic by inhalation, in contact with skin and if

swallowed.

R39/23/24/25: Toxic: danger of very serious irreversible

effects through inhalation, in contact with skin and if

swallowed.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety

LEISHMAN STAIN DYE204



precautions. It does not represent any guarantee of the properties of the product. Solmedia Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.