

MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name:	DPX Mountant High Viscosity Specially Thickened
Product code:	REA213
Brand:	Solmedia Ltd

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: PC21: Laboratory chemicals.

1.3 Details of the supplier of the safety data sheet

Name of Supplier: Address of Supplier:	Solmedia Ltd. Unit 2, Vernon Drive Battlefield Enterprise Park Shrewsbury SY1 3TF
	UK
Telephone:	0844 80 80 900
Email:	labsupplies@solmedialtd.com

1.4 Emergency telephone number

Emergency Phone: +44 (0)844 80 80 900

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Skin Irrit. 2: H315; Acute Tox. 4: H312+332; Flam. Liq. 3: H226

Most important adverse effects:

Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation.

2.2 Label elements

Hazard statements:	H226: Flammable liquid and vapour.	
	H312+332: Harmful in contact with skin or if inhaled.	
	H315: Causes skin irritation.	
Signal words:	Warning	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	





Precautionary statements:

	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.
	P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P312: Call a POISON CENTRE or doctor if you feel unwell.
	P370+378: In case of fire: Use suitable media for extinction.
2.3 Other hazards	
	In use, may form flammable / explosive vapour-air mixture.
PBT:	This product is not identified as a PBT/vPvB substance.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients:

XYLENE

EINECS	CAS	CLP Classification Perce	
215-535-7	1330-20-7	Flam. Liq. 3: H226; Acute Tox. 4: H332;	70-90%
		Acute Tox. 4: H312; Skin Irrit. 2: H315	

SECTION 4: First aid measures

4.1 Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.



Inhalation:Remove casualty from exposure ensuring one's own safety whilst
doing so. Consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact:	There may be irritation and redness at the site of contact.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.	

Delayed / immediate effects:

Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

Flammable. In combustion emits toxic fumes. Forms explosive airvapour mixture.

5.3 Advice for firefighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2 Environmental precautions

Do not discharge into drains or rivers. Contain the spillage using bunding.



6.3 Methods and materials for containment and cleaning up

Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4 Reference to other sections

Refer to section 8 of SDS.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build-up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8-hour TWA	15 min. STEL	8-hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

DNEL / PNEC No data available.

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.



Hand protection:	Impermeable gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Impermeable protective clothing.	
Environmental:	Not applicable.	

SECTION 9: Physical and chemical properties

SECTION 9: Physical and chemical properties			
9.1 Information on basic phy	vsical and chemical properties		
State:	Liquid		
Flash point [°] C:	29		
9.2 Other safety information	I		
	Not applicable		
SECTION 10: Stability and rea	activity		
10.1 Reactivity			
	Stable under recommended transport or storage conditions.		
10.2 Chemical stability			
	Stable under normal conditions. Stable at room temperature.		
10.3 Possibility of hazardous	reactions		
	Hazardous reactions will not occur under normal transport or storage conditions.		
	Decomposition may occur on exposure to conditions or materials listed below.		
10.4 Conditions to avoid			
	Heat. Hot surfaces. Sources of ignition. Flames.		
10.5 Incompatible materials			
	Strong oxidising agents. Strong acids.		
10.6 Hazardous decompositi	on products		
	In combustion emits toxic fumes.		

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Hazardous ingredients:



XYLENE

ORL	MUS	LD50	2119	mg/k
ORL	RAT	LD50	4300	mg/k
SCU	RAT	LD50	1700	mg/k

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.	
Delayed / immediate effects:		
	Immediate effects can be expected after short-term exposure.	

Other information: Not applicable.

SECTION 12: Ecological information

12.1 Toxicity

No data available.

12.2 Persistence and degradability

Biodegradable.

12.3 Bioaccumulative potential

No bioaccumulation potential.

12.4 Mobility in soil

Readily absorbed into soil.

12.5 Results of PBT and vPvB assessment

This product is not identified as a PBT/vPvB substance.

12.6 Other adverse effects

Negligible ecotoxicity.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.
Recovery operations:	Not applicable.
Disposal of packaging:	Dispose of as unused product.
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information

14.1 UN number

1993

14.2 UN proper shipping name

	FLAMMABLE LIQUID, N.O.S.	
14.3 Transport hazard class(es)		
	3	
14.4 Packaging group		
	III	
14.5 Environmental hazards		
	No	
Marine pollutant:	No	
14.6 Special precautions for user		
Special precautions:	No special precautions.	
Tunnel code:	D/E	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.



SECTION 16: Other information

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and 3:

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

H332: Harmful if inhaled.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solmedia Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.